

white c evo.

Configurable, traceable uniform distribution.

adapt each level.

White C EVO combines configurable compartments with a 21.5-inch touchscreen. Levels can hold different compartment sizes for uniform sets, clogs, jackets and other garments.

up to 600

Garments in sets, depending on compartment configuration.



White C EVO

at a glance.

Flexible levels	12, 15, 18, 22 or 30 compartments per level
Operator interface	21.5-inch touchscreen
Remote diagnostics	Monitor hardware and software components
Construction	Steel/aluminium structure with ABS exterior

white c evo specifications.

Specification	Technical data
Power supply - CE	230 V single phase, 50 Hz
Power supply - UL	115 V single phase, 60 Hz
Power consumption	0.15 kW nominal
Protection / insulation	Structure IP12; electrical panel IP22; Class I
Gear motor	Lifetime lubrication
Electrical outlet	Industrial plug IEC 60309-1
Empty weight	290-320 kg, depending on configuration
Structure	Painted steel / aluminium and ABS
Connectivity	Ethernet
Touchscreen	21.5-inch
Operating system	Windows 10 Embedded IoT LTSC
Standard badge reader	Magnetic stripe reader, tracks 1-2-3
Average delivery time	Less than 5 seconds
Garment identification	Barcode; HF and UHF RFID

Capacity depends on compartment configuration and whether garments are dispensed in sets.

model comparison.

Configuration	Single garments	Garments in sets	Cell L x D x H, mm
120	120	240	212 x 360 x 150
150	150	300	180 x 360 x 150
180	180	360	150 x 360 x 150
220	220	440	120 x 360 x 150
300	300	600	90 x 360 x 150

Configuration can combine different compartment sizes.